

FULL HEIGHT TURNSTILE STAINLESS STEEL

TS-FH1

1 Lane

Bi-direction



SPECIFICATIONS

Size: 1400x1200x2310mm

Unlock time: 0.2s

Pass rate: 30 person/min

Pass width: $\leq 650\text{mm}$

Input: 100-240V

Motor: Voltage: 24V

Environment: $-25 - +70$

Power consumption: 30W



Functions

- Bi-directional passage
- Electrical controls for both directions
- Integration with any identification or access control system
- Automatic reset of barrier wings after each passage
- Push button switch override controls for emergency situations
- Cable or wireless remote control
- Indoor application
- Modular plug-in electronics provides for easy and quick repairs



Technical Specifications



Size	2310*1200*1400mm
Material	1.5mm 304 SUS hairline 400
Pass Width	600mm
Passage direction	Single directional/Bi-directional
Pass rate	30-35 persons/minute
Operating time	0.2 seconds
Power input	AC100-240V,50/60HZ
Working voltage	24V
Working humidity	30%~95%
Working temperature	-40°C~+70°C
Working environment	Indoor/ Outdoor available
Communication interface	RS485, Dry contact
Mechanism	Solenoid Lock mechanism+cam+drapper
MCBF	5,000,000 Cycles
Application	Factory, Stadium, GYM, Museum, etc

