



Embedded binocular face recognition terminal

ACS-FR-HG06

Binocular 100W Camera



Reject photo card



Reject video card replacement



Technical Parameters:

Processor	Dual-core A7-1.2GHZ
System	LINUX
RAM	256MB
Storage	256MB
Camera	Binocular 1 million
Amount of users	2000
Face capacity	2000
Password capacity	2000
IC/ID	2000
Recording capacity	200,000 records
Identifying	Face/card/password
Verification speed	≤ 0.3s
Display method	4-inch wide viewing angle display (480*800)
Touch screen	Capacitive touch screen
Communication	USB 2.0, U disk, 10M/100M adaptive, WiFi
Language	English (other languages can be customized)
Access control output	Wiegand 26/34, RS485, door sensor, electric lock, door open button, alarm, doorbell
Power supply	DC12V/2A
Use distance	0.5~2 M (distance of living body 0.5~1 M)
Operating temperature	-30°C~60°C
Working humidity	0% ~ 90%
Antistatic	contact ≥4KV air ≥8KV
Characteristics	Binocular live detection
Use environment	indoor



4 Inch Touch
Screen




Dynamic Face
Recognition



IC Card
Capacity 2000



HD Dual Camera



U Disk Attendance



TBC / IP
Communication



Voice
Announcements



Password Open
The Door



Binocular face recognition terminal

